




The Vivotek PT1111M/1121M is a cost effective and easy-to-install Pan/Tilt CCTV camera ideal for CCTV installers. Unlike the traditional bulky Pan/Tilt CCTV camera, Vivotek PT1111M/1121M with a stylish shape is extremely compact and light-weight. Built-in "Pelco D" protocol, PT1111M/1121M is capable of working with most DVRs, controllers and video servers. High quality 1/3" CCD sensor provides the sharp image while the wide-range pan/tilt effectively increases the viewing angle. The included ceiling mount kit and available remote control make the installation and operation much easier!

Features

- RS-485 control interface
- Use "Pelco D" protocol; work with most DVRs and Video Servers
- Compact size and light-weight
- Cost effective and easy to install
- Wide-range Pan/Tilt operation
- Camera ID setting (1~254)
- High quality 1/3" CCD sensor
- Included ceiling mount kit
- IR remote control available

Technical Specifications PT1111M/PT1121M






Image sensor	1/3" Color CCD	Pan Angle	-135°~ +135°
Picture Elements	NTSC: 512*492/ PAL: 512*582	Pan Speed	2 [°] ~ 65 [°] /sec.
Horizontal Resolution	380 TV Lines	Tilt Angle	-90°~ +45°
H. Sync Frequency	NTSC: 15.734 KHz, PAL: 15.625 KHz	Tilt Speed	6°~ 30°/sec.
V. Sync Frequency	NTSC: 59.94 KHz, PAL: 50 KHz	Control Interface	RS-485
Synchronization	Internal	Address Setting	1~254
Minimum Illumination	1.0 Lux at F2.0	Dimensions	115mm(L)*105mm(W)*110mm(H)
Back Light Compensation	ON/OFF switch	Weight	Net. 308g.
Electronic Shutter	AUTO, Range: 1/50(1/60) ~ 1/100,000 sec.	Power	12V DC
Auto Gain Control	AUTO	EMI & Safety	CE,FCC
Video Output	1 Vp-p, 75 Ohms		,
Lens	Standard: 6mm/F1.8 Option: 3.6, 8, 12 mm/F2.0		

CCTV CAMERA

All specifications are subject to change without notice.
All other trademarks are owned by their respective companies.





6F,No.192,Lien-Cheng Rd., Chung-Ho,Taipei County,Taiwan Tel:+886 2 82455282 E-mail:sales@vivotek.com Web:www.vivotek.com

